#### § 157.25

- (1) Submit to the Commandant (G-MOC), U.S. Coast Guard, Washington, D.C. 20593-0001—
- (i) A letter from the authority that assigns the load line to the vessel finding that the location of the segregated ballast tanks is acceptable; and
- (ii) Plans and calculations to substantiate compliance with the segregated ballast capacity requirements in §157.09(b); or
- (2) Submit to the Officer in Charge, Marine Inspection, of the zone in which the first U.S. port call is made, a letter or document from the government of vessel's flag state certifying that the vessel complies with the segregated ballast capacity requirements in §157.09(b) or Regulation 13 of the MARPOL 73/78.
- (c) On January 1, 1986, or 15 years after the date it was delivered to the original owner, or 15 years after the completion of a major conversion, whichever is later, before that vessel enters the navigable waters of the United States, the owner or operator of an existing foreign vessel under §157.10c(b)(1) or §157.10c(c)(1) must—
- (1) Submit to the Commandant (G-MOC), U.S. Coast Guard, Washington, D.C. 20593-0001—
- (i) A letter from the authority that assigns the load line to the vessel finding that the location of the segregated ballast tanks is acceptable; and
- (ii) Plans and calculations to substantiate compliance with the applicable segregated ballast capacity requirements in §157.09(b) or §157.10c(d); or
- (2) Submit to the Officer in Charge, Marine Inspection, of the zone in which the first U.S. port call is made a letter from an authorized CS or the government of the vessel's flag state certifying that the vessel complies with the segregated ballast capacity requirements in §157.09(b) or §157.10c(d).

(Reporting and recordkeeping requirements approved by the Office of Management and Budget under control number 2115–0520)

[CGD 82-28, 50 FR 11626 and 11630, Mar. 22, 1985, as amended by CGD 88-052, 53 FR 25122, July 1, 1988; CGD 96-026, 61 FR 33668, June 28, 1996; USCG-2000-7641, 66 FR 55573, Nov. 2, 2001]

## **Subpart C—Vessel Operation**

### § 157.25 Applicability of subpart C.

- (a) This subpart applies to each vessel to which this part applies of 150 gross tons or more, unless otherwise indicated, that carries crude oil or products in bulk as cargo. This subpart does not apply to a foreign vessel which remains beyond the navigable waters of the United States and does not transfer oil cargo at a port or place subject to the jurisdiction of the United States.
- (b) Sections 157.29, 157.31, 157.37(a)(5), 157.37(a)(6) and 157.43 apply to foreign vessels when they discharge into the navigable waters of the United States.
- (c) Sections 157.35, 157.37, except paragraphs (a)(5) and (a)(6), 157.39, 157.45, and 157.47 do not apply to foreign vessels.

[CGD 76-088b, 48 FR 45720, Oct. 6, 1983, as amended by CGD 90-051, 57 FR 36244, Aug. 12, 1992]

## §157.26 Operation of a tank vessel in violation of regulations.

No person may cause or authorize the operation of a tank vessel in violation of the regulations in this part.

[CGD 77-058b, 45 FR 43708, June 30, 1980]

# § 157.27 Discharges: Tank vessels carrying oil exclusively on rivers, lakes, bays, sounds, and the Great Lakes, and seagoing tank vessels of less than 150 gross tons.

Unless a tank vessel carrying oil exclusively on rivers, lakes, bays, sounds, and the Great Lakes, or a seagoing tank vessel of less than 150 gross tons discharges clean ballast or segregated ballast, the vessel must:

- (a) Retain on board any oily mixture;
- (b) Transfer an oily mixture to a reception facility.

## § 157.28 Discharges from tank barges exempted from certain design requirements.

The person in charge of a tank barge exempted under §157.08(g) from the requirements in §§157.11, 157.13, 157.15, and 157.23 shall ensure that while the barge is proceeding en route:

(a) Cargo tanks are not ballasted or washed; and